

## Chain Stock FWD

All plastic, windows, lights and all other flammable material must be removed/ stock gas tank must be removed. Dash may remain in place.

1. FWD Cars Only
2. No welding unless noted.

### Cage :

1. 4 point cage allowed : 1 dash bar, 1 sidebar per side, 1 back seat bar allowed.
2. Gas tank must be mounted off back seat bar. Must be a minimum of 6" away from sheet metal.  
**Gas Tank must be metal no plastic tanks allowed.**

### Body Mounts must remain stock.

1. If body mount is rusted out you may replace it with same size bolt.
2. Stock body pucks must remain in place.

### May chain or wire doors shut.

1. 2 chains per door
2. 6 chains or wire in the hood and trunk
  - a. 2 to frame allowed
  - b. 4 sheet metal to sheet metal

### After Market:

1. Gas/Brake Pedals Allowed
2. Shifter Allowed
3. Headers Allowed

\*No other aftermarket parts allowed!

### Bumpers:

1. Stock bumper for the car you are running.
2. If plastic may change with tin style bumper off another car.
3. Bumpers may be welded to end of frame. Absolutely nothing inside of the frame!!
4. May run a 3x3 1/8 inch thick tube as a front bumper.

**Tires:**

1. Any tire allowed
  - a. No bead locks allowed!

**Pre – Ran Cars :**

1. 2 – 5 x 5 ¼ plates allowed to weld bumper back on.

**No Welding of :**

1. Struts
2. Tie Rods
3. Motor Mounts
4. Doors